

DECLARATION OF PERFORMANCE

Declaration of Performance No: PB-SG-01

1. Identification of product:

Dry pressed ceramic floor tile, $E_b \le 0.5 \%$

2. Intended use(s):

For internal and external floorings

3. Name and contact address of the manufacturer:

Ege Seramik San. ve Tic. A.Ş Ankara Asfaltı 26. Km Kemalpaşa / İzmir Türkiye

Tel: +90 232 878 17 00 Fax: +90 232 878 12 54

www.egeseramik.com info@egeseramik.com

4. System or systems of assesment and verification of constancy of performance of the construction product :

System 4

5. Declared performance

Essential characteristics	Performance	Harmonised technical spesification
Reaction to fire	A1 _{fl}	
Release of dangerous substance, for		
- Cadmium	NPD	
- Lead		
Breaking strength	Thickness ≥ 7.5 mm min. S:1300 N Thickness < 7.5 mm min. S:700 N	
Slipperiness	Slipperiness value appears on the product barcode label	
Tactility	NPD	EN 14411:2012
Bond strength/ adhesion for:		
Cementitious adhesive, type C2	Min.1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze -thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 5

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Ali Rıza AKLIKLI

Quality Assurance & Control Manager

28.05.2013/İzmir/Turkey

EGE SERAMÍK
SAN VE TÍC.A.Ş
Arisra Adati 26 Km komptoba (DAST
TEODZ 2071 (D) Fala (D252 2011)29